



# ECO CE PLATE

Material - Aluminium same as original Hobbit

THIS PLATE FITTED TO **ALL** ECO HOBBIT STOVES

USING SHORT SELF TAPPING SCREWS


BS EN 13240 : 2001/A2:2004


Room Heater  
Fired By Solid Fuel

---

**Salamander Model 1901 eco**  
**Ecodesign Multifuel Stove**

Fuel types	Wood, Manufactured Smokeless Fuel	
Nominal Heat Output	Wood	4.1 kw
	Manufactured Smokeless Fuel	4.1 kW
Total net energy efficiency	Wood	79.4 %
	Manufactured Smokeless Fuel	81.4 %
Distance to adjacent combustable materials (Without heat shields)	Side	400 mm
	Rear	450 mm
Distance to adjacent combustable materials (With heat shields)	Side	150 mm
	Rear	100 mm
Emission of CO in combustion products	Wood	0.09 %
	Manufactured Smokeless Fuel	0.09 %
Flue gas temperature	Wood	274 °C
	Manufactured Smokeless Fuel	240 °C

The appliance is capable of intermittent operation  
The appliance cannot be used in a shared flue  
Follow the users manual and only use recommended fuel

---

Salamander stoves Ltd  
Rosemount, Canada Hill  
Ogwell, Devon, TQ12 6AF

REV	DATE	REVISION DESCRIPTION	BY
A	140121	UKCA added	JL





**Hobbit - Model 1901 SE eco**  
**Salamander Stoves Ltd**  
Rosemount, Canada Hill  
Ogwell, Devon, TQ12 6AF

<b>ECO CE PLATE</b>		
Name		
Drawn By	Date	Drawing No
JDL	16.10.20	1901 - 150 -A

# SE ECO CE PLATE

Material - Aluminium same as original Hobbit

THIS PLATE SUPPLIED AS A **PART ONLY** TO BE FITTED WHEN REQUIRED IN THE UK


BS EN 13240 : 2001/A2:2004


Room Heater  
Fired By Solid Fuel

---

**Salamander Model 1901 SE eco**  
**Ecodesign Multifuel Stove**

Exempt under the clean air act 1993 for use within UK smoke control areas

Fuel types	Wood, Manufactured Smokeless Fuel	
Nominal Heat Output	Wood	4.1 kw
	Manufactured Smokeless Fuel	4.1 kW
Total net energy efficiency	Wood	79.4 %
	Manufactured Smokeless Fuel	81.4 %
Distance to adjacent combustable materials (Without heat shields)	Side	400 mm
	Rear	450 mm
Distance to adjacent combustable materials (With heat shields)	Side	150 mm
	Rear	100 mm
Emission of CO in combustion products	Wood	0.09 %
	Manufactured Smokeless Fuel	0.09 %
Flue gas temperature	Wood	274 °C
	Manufactured Smokeless Fuel	240 °C

The appliance is capable of intermittent operation  
The appliance cannot be used in a shared flue  
Follow the users manual and only use recommended fuel

---

Salamander stoves Ltd  
Rosemount, Canada Hill  
Ogwell, Devon, TQ12 6AF

REV	DATE	REVISION DESCRIPTION	BY
A	140121	UKCA added	JL



**Hobbit - Model 1901 SE eco**

**Salamander Stoves Ltd**

Rosemount, Canada Hill  
Ogwell, Devon, TQ12 6AF

Name		
<b>SE ECO CE PLATE</b>		
Drawn By	Date	Drawing No
JDL	16.10.20	1901 - 151 - A